


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : G06F 13/40		A1	(11) International Publication Number: WO 00/67137
			(43) International Publication Date: 9 November 2000 (09.11.00)
(21) International Application Number: PCT/EP00/03796 (22) International Filing Date: 25 April 2000 (25.04.00) (30) Priority Data: 99201337.5 29 April 1999 (29.04.99) EP 99202447.1 26 July 1999 (26.07.99) EP (71) Applicant (for all designated States except US): KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (72) Inventors; and (75) Inventors/Applicants (for US only): WAUTERS, Piet, S. [BE/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). LENAERTS, Jean, L., J. [BE/NL]; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). (74) Agent: DE HAAS, Laurens, J.; Internationaal Octrooibureau B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).			(81) Designated States: JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: DEVICE FOR USE AS STAND-ALONE DEVICE AND AS SLAVE DEVICE IN A DATA BUS SYSTEM



(57) Abstract

A device is provided for use in a data bus system like a USB bus system. The device (14) can be coupled to a host (10) via a bus cable (12) that comprises a data transfer conductor (124) and power supply conductors (120-122). The device (14) detects whether a power supply is connected to the power supply conductors (120-122). Dependent on whether or not connection of the power supply has been detected, device (14) starts operating in a slave mode or in a stand-alone mode respectively. In a slave mode the device (14) waits for commands received via the data transfer conductor. In the stand-alone mode the device (14) operates independent from communication via the cable. Preferably, the device signals back to the host whether it is in the slave mode by enabling pull-up of a potential of the data transfer conductor (124). In an embodiment, detection and signaling is controlled via a single control node (149).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Device for use as stand-alone device and as slave device in a data bus system.

The invention relates to device for use in data bus system such as a USB bus system.

The USB system is known from PCT patent application WO99/08422 (assigned to the same applicant as the present application; applicant's ref. No. PHN 16496).

5 A USB bus system comprises a host station connected to a device via a USB cable. The connection may be indirect, via hub station connected to the USB cable, or direct, with the host station itself connected to the USB cable.

The USB cable contains a first and a second power supply conductor and a first and a second data transfer conductors. The power supply conductors serve to supply
10 power from the host station to the device (or from any intermediary station if the device is connected indirectly). USB devices such as a mouse or a keyboard power their operation with the power received from the USB cable. Other devices may have their own power supply and don't use the power from the USB cable.

The data transfer conductors serve for communication of data between the host
15 and the device. The data includes commands send from the host to the device to control the device and data such as mouse position updates or keystrokes. The USB bus system is hierarchical in the sense that all message communication via the data transfer conductors is controlled by the host and the device operates as a slave, which waits for instructions received from the host.

20 The data transfer conductors also serve to signal attachment of the device to the USB cable. Any device may be attached to the USB cable at any time, also after the host station has started up. The bus system pulls the potential of the data transfer conductors toward that of the first power supply conductor. The device contains a resistor connected between one of the data transfer conductors and the second power supply conductor, so that
25 the potential of the data transfer conductor is pulled toward that of the second power supply conductor when the device is attached to the USB cable. The host station monitors the potential of the data transfer conductor (directly or by means of a hub station). If the potential of the data transfer conductor shifts towards that of the second power supply conductor, a "connect condition" is said to occur, signaling to the host station that a device has been

attached. Once the host station detects the "connect condition", the host station starts communicating with the device, in order to set-up the device and to set the device into action.

5 The device according to WO99/08422 has a switch in series with the second resistor. When the device is switched on the switch is initially non-conductive and it is made conductive only after the device has had time to initialize itself. Thus the device creates a delay between attachment and the occurrence of the "connect condition". The delay gives the device the opportunity to initialize itself before the host can communicate with the device to
10 set it in action. When there is no host station, or the when the host station is switched-off, the device does not get into action.

 Earlier filed patent application No. EP 99201337.5 (unpublished at the time of filing the present application; assigned to the same applicant as the present patent application), which is incorporated herein by way of reference, describes how a device can be
15 used either as a hub connecting the host station to the subsystem or as a host of the subsystem. However, this earlier filed patent application does not describe the use of the power supply to detect the absence on presence of an active host station.

20 It is an object of the invention is to provide a way to make it possible to use the device also when it is not connected to an active host station via the cable.

 The device according to the invention is described in Claim 1. Preferably, the device is for use in a USB bus system. According to the invention, the device uses the presence or absence of power supply on the bus cable to decide whether to start operating in
25 a stand-alone mode or to wait for data transfer from the host station to operate as a slave. If no power is supplied via the bus cable, the device operates in the stand-alone mode.

 By "stand-alone" it is meant that the device does not operate in the bus system as "slave" of the host station. In the stand-alone mode the device operates independent from any messages from the data transfer conductors. The device starts actions that the device
30 would not take, or would only take upon command by the host station, if the host station had been detected. "Stand-alone" does not exclude the possibility that the device itself acts as host station for a bus-subsystem connected to the device. Claim 2 describes an embodiment of the device according to the invention. In this embodiment, the device disables the creation of a "connect condition" (pulling the potential of the data transfer conductor back to the potential

of one of the power supply conductors) when in the stand-alone mode. This prevents that a host station will unexpectedly try to start communication with the device when the device is attached to the bus system during operation in the stand-alone mode. In the slave mode, creation of the "connect condition" is normally enabled.

5 Claim 3 describes an embodiment of the device according to the invention that uses a single connection of the control circuit both to sense whether a host station is present and to control the generation of the "connect condition". The data transfer conductor is connected via a resistive element to a potential source to pull the potential of the data transfer conductor so as to create the connect condition. Preferably, the potential source is derived
10 from the power supply conductors.

Another embodiment of the device according to the invention is described in Claim 5. This embodiment allows the device to continue testing whether the device is attached to an active bus system, also after the device has initially entered the stand-alone mode or the slave mode. Thus, the device can switch from the stand-alone mode to the slave
15 mode or vice versa, dependent on whether or not a power supply is detected on the power supply lines during operation in the stand-alone mode or the slave mode. The device may provide for switching from the stand-alone mode to the slave mode, or for switching from the slave mode to the stand-alone mode or both.

When switching from the slave mode to the stand-alone mode or vice versa, a
20 resistive connection between the data transfer conductor and the first one of the power supply conductors is preferably switched off and on respectively, to simulate disconnect and connect of the device. In a further embodiment, the device uses a single connection to its control circuit both to monitor the power supply and to control signaling of the connect condition.

25 These and other advantageous aspects of the device according to the invention will be described in more detail using the following figures.

Figure 1 shows a bus system

Figure 2 shows an embodiment of a connect circuit

30 Figure 1 shows a bus system. The bus system comprises a host station part 10 and a device 14 connected via a cable 12. The host station part may be for example a USB host station, or part of a USB system containing a host station connected to one or more hubs,

the cable 12 being coupled to a port of a hub. The cable 12 comprises power supply conductors 120, 122 and data transfer conductors 124, 126. The device 14 has a connector 16 connecting the device 14 to the cable 12. The device 14 contains a data reception circuit 140 coupled to the data transfer conductors 124, 126 for receiving and transmitting messages via the data transfer conductors 124, 126.

The device 14 also contains a control circuit 142 (implemented for example as a suitably programmed micro-controller), a connect circuit 144 and resistors 146, 148. The control circuit 142 has an input/output connection coupled to a control input of the connect circuit 144 via a node 149. The node 149 is coupled to the power supply connections 120, 122 of the cable 12 via resistors 146, 148 respectively. The device 14 is powered by its own power supply (not shown).

In operation, the host station part 10 initially supplies a power supply voltage (e.g. 5V) across power supply conductors 120, 122. This power supply voltage may be used to power simple devices 14 that have no own power supply, such as a mouse or keyboard attached to the system. The data transfer conductors 124, 126 are connected the low voltage power supply conductor 122 via respective resistances (not shown). Thus, absent any other connections to the data transfer conductors 124, 126, the potential of these data transfer conductors 124, 126 would equal that of power supply conductor 122.

This is an initial situation, which occurs before the device 14 is switched on before the device has been attached to the host station part 10 via the cable 12. According to the USB specification, the device 14 contains a resistor (not shown in figure 1) connected to one of the data transfer conductors 124, 126 to pull up the potential of that data transfer conductor 124, 126 towards the potential of the high power supply conductor 120. Because the potential of these data transfer conductors 124, 126 is pulled resistively, it is still possible to impose data transfer signals on these conductors, by using a strong enough driver circuit. The pull-up enables the host station part 10 to detect that the device 14 has been connected to the bus system. In response, the host station part 12 will start communicating with the device via the data transfer conductors 124, 126, in order to configure the device 14. Afterwards, the host station will write or read data to and from the device and send control signals as appropriate for using the device.

Typical examples of USB devices are a mouse, a keyboard, a computer display a camera etc. If the device 14 is not attached to the host station part 10, or when the host station part 10 is not switched-on a USB device would conventionally remain inactive,

waiting until the host station part 10 is attached or switched on and starts sending messages over the data transfer conductors.

The device 14 according to the invention detects whether an active host station part 10 is attached to the connector 16 and switches to a stand-alone operating mode if this is not the case. The device 14 tests the power supply voltage supplied via the power supply conductors 120, 122 to detect whether an active host station part 10 is attached. If this power supply voltage is zero or less than a predetermined threshold, the device 14 start operating in a stand-alone mode. For example, the device may be able to operate using local information or information obtained via the internet, the device being connected to the internet via the host station part 10. When no active host station part 10 is attached, the device 14 starts operating "stand-alone" using local information. Otherwise, the device operates as a slave, receiving information (e.g. access keys) from the internet via the host station part. Of course many other applications of stand-alone vs. Slave operation are possible, such consumer audio and video equipment (video recorder, CD player, TV, audio set etc.) that is either controlled by a host as part of a system or operates stand-alone.

To select between stand-alone operation and slave operation, the control circuit 142 has a connection coupled to the power supply conductors 120, 122. The control circuit 142 switches this connection as an input, to sense whether an active host station part 16 is connected to the device 14. If an active station part 10 is connected, the resistors 146, 148 form a voltage divider. (Resistor 146 being smaller than resistor 148, so that the potential of the node 149 is closer to that of the high power supply conductor 120 than to that of the low power supply conductor 122). This results in a high voltage at the node 149, which is detected by the control circuit 142, which consequently starts sets the device to operate as a slave. If the device is disconnected from the cable 12, the connection for the high power supply conductor floats and the potential of the node 149 is pulled to the potential of the low power supply connected to the control circuit 142. As a result, the control circuit set the device 14 to operate in the stand-alone mode. Similarly, if no power supply voltage is present across the power supply conductors 120, 122 the voltage at the node 149 will be low and the device will operate in the stand-alone mode.

Preferably, this test for the presence of an active host station part 10 is repeated periodically, so that the device 14 can switch between the stand-alone mode and the slave mode, dependent on the appearance or disappearance of the power supply voltage.

When the device 14 operates in the slave mode, this mode should be made detectable for the host station part 10, by connecting a pull-up circuit to one of the data

transfer conductors 124, 146. Preferably, this pull-up circuit is disabled when the device 14 is not prepared to operate in the slave mode, for example, when the device 14 is initializing itself, when it operates in the stand-alone mode, or when the control circuit has not yet decided whether to operate in the stand-alone mode or in the slave mode.

5 For this purpose a connect circuit 144 is provided. Under control of the control circuit 142, the connect circuit 144 either pulls up the potential of one of the data conductors 124, 126 or passively or actively allows this potential to be pulled down. As shown in figure 1, a single node 149 connected to the control circuit 142 is used to control the connect circuit. This is a preferred embodiment, because it economizes the use of output pins of the control
10 circuit 142. However, one may of course use separate inputs and outputs (not shown) of the control circuit 142, to sense the voltage on the power supply connections 120, 122 and to control the connect circuit 144 respectively.

 For use with a single node 149, the connect circuit 144 is arranged to disable the pull-up of the data transfer conductor 124, 126 when the potential of the node 149 is high
15 due to the presence of a sufficient power supply voltage on the power supply conductors 120, 122. When the device 14 is prepared to operate in the slave mode, the control circuit 142 switches its connection to the node to be an output pin that drives a low voltage to the node 149. When the voltage of the node is low, the connect circuit 144 enables pull up of the data transfer conductor 124, 126. Preferably, the connect circuit is designed to provide a delayed
20 response to rising of the potential of the node 149. Thus, the pull-up will remain active for a short time interval (of say 1 msec) if the control circuit 142 temporarily switches its connection to the node to (high impedance) input, in order to sense whether a power supply voltage is still present on the power supply conductors. This enables the periodic tests of the power supply, without disconnecting the device 14 from the system.

25 Figure 2 shows an embodiment of the connect circuit 144. The connect circuit 144 comprises a PMOS transistor 20, a resistor 22 and a capacitor 24. A main current channel of the PMOS transistor 20 is switched in series with the resistor 22 between a connection D for one of the data transfer conductor 124, 126 (not shown) and a connection VBUS for the high power supply conductor 120 (not shown). The capacitor 24 is switched in parallel with
30 the main current channel of the PMOS transistor 20. Also shown in figure 2 are the resistors 146, 148, the node 149 and a connection GND for the low power supply conductor 122 (not shown) from figure 1.

 In operation the resistor 22 serves to pull up the potential of the data transfer conductor 124, 126 when PMOS transistor 20 is conductive. The voltage of the node 149

controls whether the PMOS transistor 20 is conductive. Resistors 146 and 149 are chosen so that the gate source voltage of PMOS transistor 20 will be below its threshold voltage when the connection of the control circuit 142 to the node 149 is switched as input. In this case, the data transfer conductor 124, 126 will not be pulled up by resistor 20, so that the host station part 10 will observe the cable as not connected.

When the control circuit 142 switches its connection to the node to output and pulls the voltage of the node 149 down, PMOS transistor 20 will become conductive. As a result resistor 22 will pull up the potential of the data transfer conductor 124, 126, indicating to the host station part 10 that the device is connected (and prepared to act as slave).

When the control circuit 142 briefly switches its connection to node 149 back to input, in order to sense whether power is still supplied via the power supply conductors 120, 122 of the cable, capacitor 24 will temporarily allow resistor 20 to continue to pull up the potential of the data transfer conductor. The capacitance of the capacitor 24 has been selected so that it will not discharge significantly during the time needed by the control circuit 142 to test the potential of the node 149. Thus, the control circuit can test the power supply while in the slave state without interrupting the connection to the system.

Of course, the connect circuit is only one possible embodiment to perform this function. For example, one might connect a resistor between VBUS and D and use an NMOS transistor to pull down the potential of D to signal that the device is not connected. In this case a buffer circuit (e.g. a resetable delay circuit) may be included between the node 149 and the gate of the NMOS transistor to keep the NMOS transistor non-conductive when the potential of the node 149 temporarily becomes high during testing for the presence of the power supply. A similar buffer may be used in between node 149 and the gate of PMOS transistor 20 instead of capacitor 24 to keep that transistor 20 temporarily conductive during sensing of the node 149. Also the resistor 22 may be connected to the own power supply of the device 14 (via PMOS transistor 20 in case of figure 2) instead of to the power supply VBUS received from the cable 12. However, connection to the power supply from the cable is preferred in the case of figure 2, because this makes it easier to ensure that PMOS transistor 20 operates properly.

CLAIMS:

1. A device for use in a data bus system, wherein the bus system comprises a host station, a bus cable and the device coupled to the host station via the bus cable, the bus cable comprising a data transfer conductor and power supply conductors for enabling the device to obtain operating power from the bus system via the bus cable, the device comprising a connector for coupling the device to the bus cable, and a control circuit coupled to the connector, wherein the control circuit is arranged to detect whether a power supply is connected to the power supply conductors and to start waiting in a slave mode for commands received via the data transfer conductor or to start operating in a stand-alone mode, dependent on whether or not connection of the power supply has been detected respectively.

2. A device according to Claim 1, wherein the bus system comprises a pull circuit for pulling a potential of the data transfer conductor away from a potential of a first one of the power supply conductors, the bus system being arranged to detect whether or not the potential of the data transfer conductor is pulled back to the potential of the first one of the power supply conductors via the bus cable, so as to determine whether the device is connected to the bus cable, wherein the device comprises a pull back circuit for pulling back the potential of the data transfer conductor to the potential of the first one of the power supply conductors, the control circuit enabling and disabling the pull back circuit when operating in the slave mode and the stand-alone mode respectively.

3. A device according to Claim 1, wherein the bus system comprises a pull circuit for pulling a potential of the data transfer conductor away from a potential of a first one of the power supply conductors, the bus system being arranged to detect whether or not the potential of the data transfer conductor is pulled back to the potential of the first one of the power supply conductors via the bus cable so as to determine whether the device is connected to the bus cable, the device comprising a first resistive element and a switching element, connected in series between the data transfer conductor and a pull back potential source, the device comprising a node coupled to a control electrode of the switching element, a second and third resistive element coupled between the node and the first one and a second

one of the power supply conductors respectively, so that the switching element is non-conductive when a potential of the node is affected only by the power supplied via the power supply conductors via the second and third resistive element, the control circuit having an I/O connection coupled to the node, the control circuit switching the I/O connection as an input to
5 detect whether power is supplied via the power supply conductors and the control switching the I/O connection as an output to make the switching element conductive to enable pull back.

4. A device according to Claim 3, wherein the pull back potential source is the
10 first one of the power supply conductors.

5. A device according to Claim 1, wherein the control circuit is arranged to detect repeatedly whether power is supplied via the power supply conductors when the device operates in the slave mode or the stand-alone mode, the control circuit switching from
15 the slave mode to the stand-alone mode and/or vice versa when absence or presence of power supply is detected respectively.

6. A device according to Claim 5, wherein the bus system comprises a pull circuit for pulling a potential of the data transfer conductor away from a potential of a first
20 one of the power supply conductors, the bus system being arranged to detect whether or not the potential of the data transfer conductor is pulled back to the potential of the first one of the power supply conductors via the bus cable so as to determine whether the device is connected to the bus cable, wherein the device comprises a pull back circuit for pulling back the potential of the data transfer conductor to the potential of the first one of the power
25 supply conductors, the control circuit enabling and/or disabling the pull back circuit when switching from the stand-alone mode the slave mode or vice versa respectively.

7. A device according to Claim 6, wherein the pull back circuit comprises a first resistive element and a switching element, connected in series between the data transfer
30 conductor and a pull back potential source, a delay element for holding a voltage across the switching element for a limited time interval after the switching element is signaled to switch from conductive to non-conductive, the device comprising a node coupled to a control electrode of the switching element, a second and third resistive element coupled between the node and the first one and a second one of the power supply conductors respectively, so that

the switching element is non-conductive when power is supplied via the power supply conductors and a potential of the node is affected only via the second and third resistive element, the control circuit having an I/O connection coupled to the node, the control circuit switching the I/O connection as an input to detect whether power is supplied via the power supply conductors and the control switching the I/O connection as an output to make the switching element conductive when the device waits in the slave mode.

8. A device according to Claim 1, wherein the bus system is a USB bus system.

1/1




FIG. 1




FIG. 2

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 G06F13/40

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, IBM-TDB, COMPENDEX, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y A	US 5 784 581 A (HANNAH ERIC C) 21 July 1998 (1998-07-21) column 1, line 61 - line 67; figures 5,7 column 2, line 12 - line 27 column 5, line 24 - line 43 column 6, line 4 - line 18 ---	1,5,8 2-4,6,7
Y A	WO 99 08422 A (KONINKL PHILIPS ELECTRONICS NV ; PHILIPS AB (SE)) 18 February 1999 (1999-02-18) cited in the application page 2, line 29 - line 34 page 3, line 28 - line 33 page 4, line 5 - line 8 -----	1,5,8 2-4,6,7

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- * "A" document defining the general state of the art which is not considered to be of particular relevance
- * "E" earlier document but published on or after the international filing date
- * "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- * "O" document referring to an oral disclosure, use, exhibition or other means
- * "P" document published prior to the international filing date but later than the priority date claimed

- * "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- * "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- * "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * "&" document member of the same patent family

Date of the actual completion of the international search

25 August 2000

Date of mailing of the international search report

04/09/2000

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Henneman, P

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 00/03796

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5784581	A	21-07-1998	NONE	
WO 9908422	A	18-02-1999	EP 0940023 A	08-09-1999

This Page Blank (uspto)

1/1




FIG. 1




FIG. 2

This Page Blank (uspto)